

LEED® Product Statement

Effective Date: 10/01/15

The LEED® (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings.

GlazeGuard® 250 WR, manufactured by Citadel Architectural Products, Inc., carries the following attributes under the context of this standard:

- The product is manufactured in Indianapolis, IN.
- The composite panel is warranted for a period of 5 years.
- Polyester and Acrylic Urethane painted finishes are warranted for a period of 5 years.
- Kynar 500[®] painted finishes are warranted for a period of 30 years.
- Anodized finishes are warranted for a period of 20 years.
- The bonding agent used contains no VOCs, no formaldehyde, is non-hazardous, chemically inert, and is 100% solid (no solvents).

In addition, the following information can be used to determine the level of contribution towards satisfying MR Credit 4.1 and MR Credit 4.2(1).

GlazeGuard® 250 WR

		Recycled Content By Weight	
Composition ⁽²⁾	Weight (lbs/ft²)	Post-Consumer	Post-Industrial ⁽⁴⁾
Prefinished Textured AluminumHigh Density PolypropylenePrefinished Textured Aluminum	0.61	1.2%	17.1% to 21.1%
Prefinished Smooth Aluminum High Density Polypropylene Prefinished Smooth Aluminum	1.00	0.8%	35.2% to 37.7%

⁽¹⁾ MR Credit 4.1 and MR Credit 4.2 are based upon recycled content (as defined by the Green Building Rating System For New Construction & Renovations, ver 2.2) and are used to determine the overall dollar value of recycled material within the building.

LEED® is a registered trademark of USGBC.





⁽²⁾ General composition listed. For a detailed listing of components, refer to the Product Data Sheet.

⁽³⁾ Due to variables within the manufacturing process, recycled content is based upon an average.

⁽⁴⁾ Post-Industrial is also referred to as Pre-Consumer.